

Connect Austria gibt nachstehend die erbetenen Schnittstellenbedingungen bekannt:

## 1. PSTN/ISDN

### ISDN Primary Rate

- **ITU-T G.703**; Recommendation G.703; PHYSICAL/ELECTRICAL CHARACTERISTICS OF HIERARCHICAL DIGITAL INTERFACES
- **ITU-T Q.930**; Recommendation Q.930; DIGITAL SUBSCRIBER SIGNALLING SYSTEM No. 1 (DSS 1) – ISDN USER-NETWORK INTERFACE LAYER 3 – GENERAL ASPECTS
- **ITU-T Q.931**; Recommendation Q.931; DIGITAL SUBSCRIBER SIGNALLING SYSTEM No. 1 (dss 1) – ISDN USER-NETWORK INTERFACE LAYER 3 SPECIFICATION FOR BASIC CALL CONTROL
  
- **ETS 300 102-1**; Integrated Services Digital Network (ISDN); User-network interface layer 3 specifications for basic call control
- **ETS 300 196**; Integrated Services Digital Network (ISDN); Generic functional protocol for the support of supplementary services. DSS1 protocol
  
- **ETS 300 207-1**; Integrated Services Digital Network (ISDN); Diversion Supplementary Services DSS1 protocol Part 1: Protocol Specification

## 2. Air-Interface

- ETSI GSM 4.01 - 4.10 und 5.xx